

CARATTERISTICHE CU-BOX - 60Hz

Type	Power		Voltage [V]	Start Capacitor [mF]	Run Capacitor [mF]	Weight		Dimension	
	[Hp]	[kW]				[kg]	[lb]	[mm]	[in]
CU-BOX05-61	1/2	0.37	110/115	250-300 (125 V)	-	1.2	2.6	130 x 77 x 215	5.1 x 3 x 8.5
CU-BOX05-62	1/2	0.37	220/230	59-71 (250 V)	-	1.2	2.6	130 x 77 x 215	5.1 x 3 x 8.5
CU-BOX07-61	3/4	0.55	110/115	250-300 (125 V)	-	1.2	2.6	130 x 77 x 215	5.1 x 3 x 8.5
CU-BOX07-62	3/4	0.55	220/230	86-103 (250 V)	-	1.2	2.6	130 x 77 x 215	5.1 x 3 x 8.5
CU-BOX10-62	1	0.75	220/230	105-126 (250 V)	-	1.2	2.6	130 x 77 x 215	5.1 x 3 x 8.5
CU-BOX15-62	1.5	1.1	220/230	105-126 (250 V)	10 (400 V)	2.5	5.5	205 x 240 x 148	8.1 x 9.5 x 5.8
CU-BOX20-62	2	1.5	220/230	105-126 (250 V)	20 (400 V)	2.5	5.5	205 x 240 x 148	8.1 x 9.5 x 5.8
CU-BOX30-62	3	2.2	220/230	208-250 (250 V)	45 (400 V)	2.5	5.5	205 x 240 x 148	8.1 x 9.5 x 5.8
CU-BOX50-62	5	3.7	220/230	270-324 (250 V)	80 (400 V)	2.5	5.5	205 x 240 x 148	8.1 x 9.5 x 5.8